











TECHNICAL INFORMATION / TEKNISK INFORMATION




Type B =
surface with "knobs"

BERGO EXCELLENCE EXTREME

Material:			Environmentally friendly recyclable UV-stabilized composite.	/ Miljövänlig återvinningsbar UV-stabiliserad komposit.
Size of tile: /Plattans storlek:		EN427	302,1 x 302,1 mm. 1 m ² / box = 11 tiles. 5 m ² / box = 55 tiles. 1,09 m ² / preassembled sheet = 4 x 3 tiles.	
Thickness of tile: /Plattans tjocklek:		EN428	14,5 mm.	
Weight: /Vikt:		EN430	1 tile: 0,47 kg. 5 m ² : 26,40 kg (Maxi-pack) 4x3 tiles: 5,64 kg (Preassembled sheets).	
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	1500 ton / 1 m ² = 15000 kg/dm ² , 235 kg / cm ²	
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8	
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5	
Slip resistance / Friction: /Halkmotstånd:		SSEN-13893	0,35	
Impact resistance: /Slagåtlighet:		ISO179/2-1eU	+23 °C = >100 kJ/m ² / -30 °C = >100 kJ/m ²	
Fire category /Brandklassning:		IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO FTP Code	Certificate No. MED-B-9103 Certificate No. MED-D-1940	

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
Maxi-pack carton	5 m ² = 55 tiles	1 pallet = 24 cartons = 120 m ²	1,30 x 0,98 x 1,75 m = 2,23 m ³ , 595 kg gross weight
Preassembled sections	1 section = 4 x 3 tiles = 1,09 m ²	1 pallet = 75 sections = 81,8 m ²	1,30 x 0,98 x 1,23 m = 1,57 m ³ , 411 kg gross weight
Bulk		84 m ²	1,30 x 0,98 x 1,21 m = 1,54 m ³ , 420 kg gross weight.



Med B, D
DNN



By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



SYSTEM
1

www.bergoflooring.com

